



SAFARI ISLAND

HG103



PRODUCT INFORMATION



Product Line	●	Digital
User Ages	●	3-12
User Capacity	●	20
Fall Height	●	150cm
Dimension	●	473cm x 825cm
Safety Area	●	107m ²
Safety Dimension	●	873cm x 1225cm
Maximum Height	●	385cm
Weight	●	kg
Safety Certificate	●	EN 1176-3

PRODUCT DESCRIPTION

The Safari Island series is a fun play world that brings little explorers together with the animals living deep in the forest. Decorated with a variety of animal figures, this series aims to nurture children's love for animals while sparking their curiosity about nature.

The courage of the lion, the strength of the elephant, the joy of the monkey, and many more wild friends are waiting for children in this series.

ACTIVITIES



Sliding



Climbing



Running



Sitting



Role Play



Thinking



Hand Skill



Socializing

Address: Yukarı Eğercili Mahallesi, Atatürk Bulvarı, No:122 Çarşamba/SAMSUN Post Code: 55500

Tel: +90 362 266 66 96 polfisan@polfisan.com.tr www.polfisan.com.tr



Made in Türkiye



SAFARI ISLAND

HG103



PRODUCT SPECIFICATION



Number of Users
•
20



Number of Roofs
•
1



Number of Slides
•
3




Number of Entrances
•
3

COLOR PALETTE



MATERIAL SPECIFICATION

- Main construction is made of steel pipes, diameter 89mm and thickness 3mm.
- Platforms are made of 18mm plywood.
- Roof, railings and panels are made of HPL (High Pressure Laminate) and UV-protected Polycarbonate panels, which are resistant to all weather conditions.
- It is produced using digital printing with high-quality UV curing inks that are resistant to all weather conditions.
- Slide surface is high-strength HDPE material with 15mm thickness. Slide walls are made of HPL.
- Tube slide is made of medium-density polyethylene material in a tunnel shape and transparent polycarbonate.
- Rope is made of polypropylene braided steel rope, diameter 16mm with 6 steel rope helices.
- Pipe and profile openings are covered with plastic injection caps.
- The metal surfaces of the product have been cleaned by sandblasting, washing, rinsing, and drying; zinc primer has been applied to increase corrosion resistance, and it has been painted with electrostatic powder coating.
- Screws are covered with plastic caps.
- Product doesn't have sharp edges and surfaces.
- Product has been produced in accordance with EN1176 standards.
- Please contact to Polifisan for updated information about product.



Top View



Side View



Front View

